

**WC 126A/166A features:**

- Rugged design maximizes productivity
- Exclusive serrated blades
- Side discharge capability
- Engineered to accommodate 48 HP diesel engine
  - Improved fuel economy
  - Lower emissions



*Side-discharge and chute reflector*



*Telescopic tongue with height-adjustable pintle ring*



*Heavy-duty folding feed table with rear jack stand and coneholder*



*Rotor-lock pin increases operator safety*

**New Equipment Sales**

210 Inverness Center Drive • Birmingham, AL 35242  
800.958.2555 Fax 205.449.4774

For more information email us at [sales@altec.com](mailto:sales@altec.com)

# Altec WC 126A/166A

## standard features

- 6" diameter chipping capacity
- 12" diameter x 12" wide cutting drum  
(12" Diameter x 16" wide drum on WC 166A)
- Banded Kevlar drive belt
- (4) serrated knife pockets spaced at 90 deg
- (4) serrated, hardened steel knives
- (4)-sided anvil provides long-lasting cutting surface
- Large flywheel shortens engine recovery time
- Fan and blower tube increase airflow and improve discharge
- Height-adjustable chute
- Side-discharge tube
- Adjustable chute deflector
- High-capacity, heavy-duty folding feed table
- Rotor-lock pin holds drum stationary to increase safety
- Composite battery box with lock
- Rear jack stand
- Fuel tank with gauge
- Telescopic tongue
- Height-adjustable pintle ring
- (2) 3/8" x 4' safety chains
- Electric break-away switch
- All controls located on curb side
- 12-volt, self-adjusting trailer brakes
- 6000 lb Torflex axle with EZ lube bearings
- Corrosion resistant powder coat finish (custom colors available)
- LED lights that conform to all applicable DOT standards
- 5000 lb trailer jack
- (2) 225/75-R15 radial tires mounted on 6-lug black wheels
- Black textured steel fenders



1550 Aerial Avenue • Creedmoor, NC 27522  
800.958.2555 • sales@altec.com

**New Equipment Sales • 1.800.958.2555**

## options

- Wheel chocks with holders
- Removable cone holder
- Flag holders
- Debris pusher
- Steel battery box
- Mounted spare tire (also available as ship loose)
- Strobe light
- Custom powder coat colors
- Toolbox
- Caster wheel jack stand
- Gas and diesel engine options
- HP ranging from 48 to 86

## general specifications

Capacity	6 in (152 mm)
Standard Engine	48 hp (36 kw)
Weight	3590 lbs (1628 kg)
Transport Length	13 ft, 3 in (4039 mm)
Operational Length	17 ft, 2 in (5232 mm)
Width	7 ft, 3 in (2210 mm)
Height	7 ft, 10 in (2388 mm)
Infeed Chute Size	26 h x 42 w in (660 x 1067 mm)
Folding Feed Table Size	44 in w x 50 in l (1118 x 1270 mm)
Feed Roller Nip Point Distance	105 in (2667 mm)
Feed Rate	200 fpm (61 mpm)
Cutting Drum Speed	2700 rpm
Fuel Tank Capacity	26 gal (98.4 L)

Altec reserves the right to improve products and the right to change, amend or delete specifications at any time, without notice or obligation.