CARLTON
STUMP CUTTERS

HEAVY DUTY

THE PROFESSIONAL'S CHOICE

Gas
Diesel
Turbo
Diesel

WALK-BEHIND

SELF-PROPELLED

TOW-BEHIND

TRACK-MOUNTED

Carlton PROFESSIONAL TREE EQUIPMENT

ABOUT CARLTON

The Carlton Company was established in 1952. From the very beginning Carlton has been committed to supplying the highest quality, most advanced machines available. Every machine offered represents this commitment. Today's Carlton machines feature everything from the most efficient drive system (Gates PolyChain® GT) to the highest quality paint available (Dupont Imron®).

Carlton X
PROFESSIONAL
TREE EQUIPMENT

Carlton products incorporate the most advanced and innovative features available anywhere. Carlton is the only stump cutter manufacturer to use self-purging tapered roller bearings on the cutter wheel and jack shafts in all models. These self-purging tapered roller bearings provide high capacity, long service life along with the ability to purge old grease without damaging the seals. Counterbalance valves in the hydraulic circuits ensure that cutter heads will not free fall and that the swing speed is the same in both directions, even on a grade. Captured pins on hydraulic cylinders along with hardened knock-in bushings help prevent wear. Even the cutter wheels are painstakingly ground flat to reduce vibration during operation. Flux-core weldments are used on the stress points for extra strength. These are just a few of the examples of how Carlton provides its customers with machines that minimize downtime and maximizes profits.

The Carlton Company manufactures a full line of stump cutters from 27-horsepower self-propelled units up to the 250-horsepower Hurricane. Carlton manufactures two hydraulically controlled self-propelled units–the highly maneuverable SP4012 and the high horsepower SP7015. The SP7015 combines the power of a tow-behind with the maneuverability of a portable. Carlton manufactures a complete line of track-mounted stump cutters. These machines are the most versatile machines built today. Every machine in our line is manufactured with the same commitment to quality components and craftsmanship.

900H *Series*

13 HP HONDA ENGINE

WALK-BEHIND

The 900 Series is the best choice when maximum portability and minimal initial investment are considerations. Design objectives for the 900 were ease of operation and low maintenance resulting in a machine that is both easy to use and very reliable.

The 900 Series utilizes industry standard cutter teeth, which makes replacement simple and very cost effective. Its small size coupled with its commercial grade construction and strong performance make the Carlton 900 a perfect choice for rental companies and top professionals alike.

Lightweight and easy to maneuver from stump to stump.

Hand Operated Disc Brake provides maximum holding power while grinding.

13-Horsepower Honda Engine provides years of service with a 3-Year Warranty.

Carlton PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	13 HP Honda
Cutter depth below ground	9"
Cutter height above ground	21"
Number of teeth on cutter wheel	12
Cutter wheel diameter with teeth	12 1/4"
Cutter wheel thickness	1/2" Blanchard ground
Cutter wheel bearings	1 1/4"
Fuel tank capacity	1.59 gallons
Tire size	4.10-3.50
Machine width	24"
Machine height	44"
Machine length	77"
Total weight	220 lbs.

SP2000 *Series*

27 HP KOHLER COMMAND

WALK-BEHIND

The SP2000 provides impressive cutting power and the ability to operate in tight working conditions. The unit combines the convenience of a self-propelled transmission with a 27-horsepower engine in an extremely narrow package width.

The SP2000 is easy to use and provides operators powerful cutting ability. The self-propelled transmission allows for both quick and powerful transport to the work area. The transmission provides infinitely variable hydrostatic speed control in both forward and reverse. The model SP2000 provides an excellent solution for hard to get to stumps.

Hydrostatic Transmission allows infinitely variable ground speed control.

Powerful, field proven Kohler 27-HP V-Twin Engine.

1/2-inch Thick Cutter Wheel, 19-inch diameter maximizes efficiency & provides ultimate cutting power.

Height Adjustable Control Handle along with finger tip control help to maximize operator efficiency.

Limited Slip Drive System senses when you need to turn. Does not sacrifice climbing power.

Carlton PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	27 HP Kohler Command
Cutter depth below ground	24"
Cutter height above ground	27"
Number of teeth on cutter wheel	16
Cutter wheel diameter with teeth	19"
Cutter wheel thickness	1/2" Blanchard ground
Cutter wheel bearings	1 7/16" Tapered Roller
Fuel tank capacity	5 gallons
Tire size	6-12
Machine width	32"
Machine height	46"
Machine length	93"
Total weight	695 lbs.
Paint	Dupont Imron with Epoxy Primer

SP4012 *Series*

27 HP KOHLER COMMAND GAS
35 HP BRIGGS-VANGUARD GAS
28.7 HP LOMBARDINI DIESEL

SELF-PROPELLED

Optional Dual Wheels are easily removed. One bolt and you are through the back gate.

The SP4012 series is a four-wheeled self-propelled unit designed to deliver maximum cutting power in hard to get to areas. A unique dual speed ground system allows the SP4012 to travel faster than any other stump cutter on the market today. The unit also boasts a 1-inch thick, 21-inch diameter cutting wheel, letting you grind faster and smoother than ever before. The SP4012 features heavy-duty construction (1,550 pounds), hydraulic steering and four-wheel stance. This combination offers unmatched stability and maneuverability.

This compact machine has a width of 35 inches, allowing it to fit easily through standard backyard gates. The SP4012 incorporates many of the features found in larger Carlton models including a direct drive hydraulic pump, hardened bushings and shafts, counter balance valves on the lift, swing and hydraulic drive circuits.

The SP4012 series is available with a variety of engine options including: a 27-horsepower Kohler Engine, 35-horsepower Vanguard, or the 29-horsepower Lombardini Diesel Engine. With its wide range of features and dependable construction, the SP4012 is designed to maximize production and profits, while minimizing downtime.

Carlton PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	27 HP Kohler Command Gas 35 HP Briggs-Vanguard Gas 28.7 Lombardini Diesel
Cutter depth below ground	13"
Cutter height above ground	34"
Cutter head swing	40" arc
Tongue extension	30"
Number of teeth on cutter wheel	20
Cutter wheel diameter with teeth	21"
Cutter wheel thickness	1" Blanchard ground
Jack shaft bearings	1 7/16" w/ Kohler 1 11/16" w/ Briggs-Vanguard or Lombardini
Cutter wheel bearings	1 7/16" w/ Kohler 1 11/16" w/ Briggs-Vanguard or Lombardini
Chip containment volume	16 cu. ft.
Fuel tank capacity	10.3 gallons
Hydraulic tank capacity	3.6 gallons
Tire size	8 ply 5.70-4
Machine width	35"
Machine height	46"
Machine length	8' 6"
Total weight	1550 w/ Kohler 1650 w/ Briggs-Vanguard or Lombardini
Paint	Dupont Imron with epoxy Primer

Hydraulic Steering allows precise control and operation while minimizing operator fatigue.

A 30-inch tongue cylinder gives the operator a more controlled progression into the stump when precision is a must like when cutting against a chain link fence or sidewalk.

Dual Speed Ground Drive System makes the SP4012 the fastest Self-Propelled machine available!

A Variety of Powerful Engines

Feather Touch Hydraulic Controls make the SP4012 easy to operate and provide optimum user control.

Large Cutter Wheel, 21-inch diameter & 1-inch thick, provides maximum cutting power and flywheel momentum.

Optional Dual Wheels are quickly removed.

Tapered Roller Bearings on jack shaft and cutter wheel provide long service life and reduced maintenance.

Proprietary Dual Motor Ground Drive eliminates troublesome chains, axles and axle bearings.

The SP4012's heavy-duty construction, such as flux-core weldments, hardened bushings and tapered roller bearings, make it the most durable stump cutter available.

SP7015 *Series*

48 HP DEUTZ DIESEL
60 HP TURBO CHARGED DEUTZ DIESEL

SELF-PROPELLED

Climb Pro Tires along with limited slip Dana Axle make the SP7015 extremely turf friendly.

Deutz Diesel Engine available in 48- or 60-horsepower models.

Patented Turntable Design provides a low center of gravity, keeps the engine level during operation and allows for a giant 70-inch swing travel.

Optional Back Fill Blade slides quickly into place, makes quick work of clean up.

Climb Pro Tires: Delivers maximum climbing power with minimal lawn damage.

Heavy Duty Dana 44 Rear Axle provides plenty of ground torque to get you to the stump.

Integrated Hydraulic Brake helps eliminate machine creep ensures more accurate cutting.

High Horsepower Self-Propelled Unit provides tow-behind power in a self-propelled unit.

The SP7015's 26 1/2-inch cutter wheel makes quick work of even the toughest stumps.

SP7015 brings high horsepower into tight places.

Wired and Wireless Remote Control: Remote option keeps the operator out of the dust, debris and noise.

The SP7015 is the most powerful and versatile self-propelled portable grinder made; combining the convenience of a narrow 35-inch backyard machine with the high horsepower of a tow-behind unit to create an extremely productive stump cutter.

The SP7015 offers a huge 70-inch cutting arc while extending below ground 15-inches and above-ground height to an amazing 43-inches. Carlton's exclusive patented turntable design keeps the weight low on the frame and the engine level during operation. This design also allows the use of a torque magnifying two-stage cutter wheel drive system. Carlton Model SP7015 is available with engine options of a 48-horsepower Deutz diesel or a 60-horsepower turbo charged Deutz diesel. The Carlton SP7015 is the perfect machine for a high volume contractor with tough to get to stumps.

Carlton PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	48 HP Deutz 60 HP Turbo Charged Deutz
Cutter depth below ground	15"
Cutter height above ground	43"
Cutter head swing	70" arc
Number of teeth on cutter wheel	32
Chip containment volume	38 cu. ft.
Cutter wheel diameter with teeth	26 1/2"
Cutter wheel thickness	1" Blanchard ground
Jack shaft bearings	1 11/16" Flange Mount
Cutter wheel bearings	2" Tapered Roller
Fuel tank capacity	9.6 gallons
Hydraulic capacity	5 gallons
Tire size	23x8.50-12
Machine width	35" w/out dual wheels 56" with duals
Machine height	52"
Machine length	10' 6"
Total weight	3500 lbs.
Paint	Dupont Imron with Epoxy Primer

SP7015TRX *Series*

60 HP TURBO CHARGED DEUTZ DIESEL

TRACK-MOUNTED

Clean Design Undercarriage allows for ample chip capacity while providing ground clearance needed when on rough terrain.

Deutz Diesel Engine
60-horsepower model.

Patented Turntable Design keeps engine low and level during operation, allows for a giant 70-inch swing travel.

Extendable and Retractable Tracks hydraulically contract from 48- to 35-inches allowing access to tight working conditions.

Rubber Tracks Deliver maximum climbing power and minimal lawn disruption.

Track Mounting delivers unmatched maneuverability, even weight distribution, 3.2 psi ground pressure, control and stability.

Four Speed Ground Drive System provides variable travel speeds up to 3.5 MPH!

Narrow 35-inch stance allows the SP7015 TRX to get into tight spaces.

Wireless Remote Control keeps the operator out of the dust, debris and noise.

The SP7015 TRX is truly a go anywhere do everything machine.

The SP7015 TRX 60-horsepower track machine features a wireless remote control, 4 speed ground drive system, traction control, and telescoping tracks.

The unit's track system hydraulically retracts from 48-inches to 35-inches so the operator can maneuver easily through tight situations like a back yard gate. The SP7015 TRX packs big cutting power in a compact unit and produces only 3.2 psi. ground pressure.

The four speed track system allows the operator to choose between high speed travel modes and high torque cutting modes at the flip of a switch. The TRX Series from Carlton are redefining versatility.

SPECIFICATIONS

Engine options	60 HP Deutz Turbo Charged
Cutter depth below ground	15"
Cutter height above ground	43"
Cutter head swing	70" arc
Number of teeth on cutter wheel	32
Chip containment volume	38 cu. Ft.
Cutter wheel diameter with teeth	26.5"
Cutter wheel thickness	1" Blanchard ground
Jack shaft bearings	1 11/16" Flange Mounted Tapered Roller
Cutter wheel bearings	2" Tapered Roller
Fuel tank capacity	9.6 gallons
Hydraulic capacity	9 gallons
Track dimension	9 1/2" X 75" Long
Ground pressure	3.2 psi
Machine width	35" Track Width Retracted 48" Track Width Extended
Machine height	57"
Machine length	10' 6"
Total weight	4300 lbs.
Paint	Dupont Imron with Epoxy Primer

SP8018TRX*Series*

78 HP TURBO CHARGED DEUTZ DIESEL

TRACK-MOUNTED

The SP8018 TRX can cut large stumps without the need to reposition.

Extremely High Horsepower (78-HP) combined with the Carlton belt drive system provides the most torque to cutter wheel available.

78-HP Deutz Diesel Engine provides enormous cutting power. German engineered and built Deutz engines are known worldwide for their durability and fuel economy.

Hydraulically Controlled Scrape Blade provides ability to spread or move chip piles for customers.

Turf Friendly Tracks are at home on both lawns and land clearing sites.

Patented Turntable Design provides a low center of gravity and allows for a giant 70-inch swing travel.

Four Speed Ground Drive System provides variable travel speeds up to 3.5 MPH!

Hydraulic Push Blade makes quick work out of clean up.

The SP8018 TRX provides 78-horsepower and features a wireless remote control, four speed ground drive capabilities, and traction control. With cutting dimensions of 43-inches above ground, 18-inches below ground, and an 80-inch sweep, this machine is unmatched in power and performance.

Carlton's exclusive turntable design provides an extremely low center of gravity and keeps the engine level during operation. This design is necessary for maneuvering in areas that are hilly and filled with debris. The machine is ideally suited for stump grinding professionals that take the, "go anywhere, do anything" approach.

SPECIFICATIONS

Engine options	78 HP Turbo Charged Deutz
Cutter depth below ground	18"
Cutter height above ground	43"
Cutter head swing	80" arc
Number of teeth on cutter wheel	32
Chip containment volume	50 cu. Ft.
Cutter wheel diameter with teeth	26.5"
Cutter wheel thickness	1"
Jack shaft bearings	2 3/16" Tapered Roller
Cutter wheel bearings	2 3/16" Tapered Roller
Fuel tank capacity	9.6 gallons
Hydraulic capacity	9 gallons
Track dimension	9 1/2" X 75" Long
Ground pressure	3.8 psi
Machine width	50"
Machine height	54"
Machine length	11 Ft.
Total weight	5420 lbs.
Paint	Dupont Imron with Epoxy Primer

Hurricane RS *Series*

140 HP TURBO CHARGED JOHN DEERE DIESEL

TRACK-MOUNTED

The hydraulically controlled blade on the Hurricane RS allows the operator to backfill the stump hole quickly and easily. The track system provides plenty of power to push even the largest piles!

140-Horsepower Turbo Charged John Deere Diesel Engine provides maximum cutting power.

Large Cutter Wheel, 31-inch diameter & 1½-inch thick, provides maximum cutting power and flywheel momentum.

Caterpillar Track Undercarriage provides a proven durable platform.

Tapered Roller Bearings in jack shaft and cutter wheel provide long service life and reduced maintenance.

Caterpillar Rubber Track Undercarriage provides optimal traction in all situations.

High Horsepower John Deere Diesels coupled with Carlton's patented drive system allows the operator to take a 6-inch bite in every pass.

Carlton manufactures 3 track models which work in a combination of residential and clearing applications, the compact SP8018 TRX, the highly versatile Hurricane RS, and the awesome Hurricane TRX.

Carlton's Hurricane RS inherits many of the performance features of the larger TRX with an emphasis on Residential Service. The Hurricane RS is shorter, narrow, lower, and lighter than the land clearing TRX yet rivals it in production.

The Hurricane RS shares Carlton's patented turret bearing design with the Hurricane TRX giving it 360-degree continuous rotation and massive cutting dimensions. The Hurricane RS is capable of cutting a full 18-foot width, 53 inches high and over 2 feet deep.

A Caterpillar track system is utilized on the Hurricane RS. This proven Caterpillar track undercarriage minimizes ground pressure and provides plenty of both climbing power and speed with its two-speed design. The rubber tracks used on the Hurricane RS are designed to help minimize turf damage.

The proportional wireless remote control, included as standard on every Hurricane RS, gives the operator precise control from up to 1,500 feet. This powerful remote allows the operator to control the machine from auxiliary equipment. This remote features feather touch controls that allow the operator to control the speed of every function right from his fingertips. This remote minimizes operator fatigue, maximizing operator efficiency over a long day.

The Carlton Hurricane RS delivers high production capacity in a Residential Service machine.

Carlton X
PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	140 Horsepower Turbo Charged John Deere Diesel
Cutting depth below ground	25"
Cutting height above ground	53"
Cutter head swing	18 feet diameter continuous rotation
Number of teeth on cutterwheel	48
Cutter wheel diameter w/teeth	31"
Cutter wheel thickness	1 1/2" Blanchard ground
Jack shaft bearings	2 7/16" Tapered Roller
Cutter wheel bearings	2 15/16" Tapered Roller
Head lift bearings	3 15/16"
Fuel tank capacity	36 gallons
Hydraulic tank capacity	31 gallons
Track width	12"
Track length	81"
Ground pressure	4.4 psi
Machine width	65"
Machine height	83"
Overall length	170"
Total weight	8500 lbs.
Paint	Dupont Imron with Epoxy Primer

HurricaneTRX*Series*

140 HP TURBO CHARGED JOHN DEERE DIESEL
175 HP TURBO CHARGED JOHN DEERE DIESEL
250 HP TURBO CHARGED JOHN DEERE DIESEL

TRACK-MOUNTED

Caterpillar Rubber Track Undercarriage provides optimal traction in all situations.

The Hurricane TRX is a versatile high volume stump cutter. This innovative unique machine gives you an unmatched combination of cutting power, maneuverability, and productivity. Many unique proprietary design features make it the perfect choice for high volume residential and light clearing applications.

The proven Caterpillar track undercarriage used on the Hurricane TRX provides maximum traction in all situations. This track drive system has two gears, low gear for maximum climbing power, and high gear for rapid ground travel when needed. The Hurricane TRX will get you to the stumps!

The rubber tracks used on the Hurricane TRX are at home on both clearing sites and turf. The long and wide footprint of the Caterpillar tracks minimizes ground pressure. This allows the machine to float across soft ground, getting you to stumps that would otherwise be inaccessible. Another advantage of the rubber track system is the minimal damage done to asphalt or concrete. The rubber tracks truly do minimize damage to any surface!

The proportional wireless remote control, included as standard on every Hurricane TRX, gives the operator precise control from up to 1,500 feet. This powerful remote allows the operator to control the machine from auxiliary equipment. This remote features feather touch controls which allow the operator to control the speed of every function right from his fingertips. This remote minimizes operator fatigue, maximizing operator efficiency over a long day. The Carlton Hurricane TRX delivers high production capacity in an extremely versatile package.

SPECIFICATIONS

Engine options	140 to 250 Horsepower Turbo Charged John Deere Diesel
Cutting depth below ground	25"
Cutting height above ground	72"
Cutter head swing	19 Ft. diameter continuous rotation
Number of teeth on cutter wheel	64
Cutter wheel diameter w/teeth	36"
Cutter wheel thickness	1 1/2" Blanchard ground
Jack shaft bearings	3 3/16" Tapered Roller
Cutter wheel bearings	2 15/16" Tapered Roller
Head lift bearings	4 7/16" Tapered Roller
Fuel tank capacity	50 gallons
Hydraulic tank capacity	42 gallons
Track width	16"
Track length	97"
Ground pressure	4 psi
Machine width	78"
Machine height	83"
Overall length	185"
Total weight	12500 lbs.
Paint	Dupont Imron with Epoxy Primer

Hydraulic Scrape Blade aids in quick clean up.

Proportional Wireless Remote Control allows operation from auxiliary equipment such as a Bobcat or pickup truck at a distance of more than 1,500 feet.

Up to 250-horsepower is available to meet customers productivity needs and stay within budget.

Continuous 360° Rotation allows cutting of a massive 19-ft width.

Patented Boom Design allows the Hurricane TRX to cut an amazing 72-inch high and over 2 feet deep.

High Horsepower John Deere Diesels coupled with Carlton's patented drive system allows the operator to take a 6-inch bite in every pass.

Hydraulic Scrape Blade lets operators move chip piles or debris quickly.

Caterpillar Rubber Track Undercarriage provides optimal traction in all situations.

Carlton's patented turret bearing design provides the Hurricane TRX with 360-degree continuous rotation. This gives the Hurricane TRX massive cutting dimensions, allowing the machine to cut a full 19-foot width.

3500D *Series*

48 HP DEUTZ DIESEL
60 HP TURBO CHARGED DEUTZ DIESEL

TOW-BEHIND

Carlton 3500D is a popular choice for power, size, price and convenience. Model 3500D is compact enough to be towed by small trucks and SUVs yet powerful enough to tackle large jobs.

The 3500D is available with either a 48- or 60-horsepower diesel engine providing plenty of power for the serious professional.

The 3500D, with its economical price, solid construction and powerful diesel options, is an unmatched value.

Optional Wired Remote distances the operator from dust, noise and flying debris.

High Horsepower Deutz Diesels

Compact Design allows the 3500D to be towed by compact vehicles.

Torsion Flex Suspension

Four Feet of tongue extension.



Carlton PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	48 HP Deutz 60 HP Turbo Charged Deutz
Cutter depth below ground	15"
Cutter height above ground	40"
Cutter head swing	80"
Tongue cylinder	48"
Number of teeth on cutter wheel	32
Chip containment volume	38 cu. Ft.
Cutter wheel diameter with teeth	26 1/2"
Cutter wheel thickness	1"
Jack shaft bearings	1 11/16"
Cutter wheel bearings	2"
Fuel tank capacity	25 gallons
Hydraulic tank capacity	4 gallons
Tire size	Good Year 205/75-R14
Machine width	60"
Machine height	70"
Machine length	11' 6"
Total weight	2900 lbs.
Paint	Dupont Imron with Epoxy primer

SP7500 *Series*

78 HP TURBO CHARGED DEUTZ DIESEL

TOW-BEHIND

The Model 7500 utilizes a Deutz four-cylinder turbo charged diesel engine to give the commercial user the power he needs. This model features a massive 31-inch cutter wheel which is 1½-inches thick, holds 48 teeth and is Blanchard ground for smoothness. The cutter wheel combined with the turbo charged diesel power give Carlton Model 7500 unmatched performance. Carlton's solid construction and use of the finest components give the 7500 unmatched quality.

Optional Remote Control

Deutz Diesel Engine provides enormous cutting power. German engineered and built Deutz engines are known worldwide for their durability and fuel economy.

Massive 31-inch Diameter by 1 1/2-inch cutter head makes cutting smooth and powerful.

Five Feet of Tongue Extension allows the 7500 to cut the largest stumps without repositioning.

Torsion Flex Suspension makes all Carlton tow-behind units ride smoothly.

Carlton PROFESSIONAL TREE EQUIPMENT

SPECIFICATIONS

Engine options	78 HP Turbo Charged Deutz Engine
Cutter depth below ground	24"
Cutter height above ground	46"
Cutter head swing	92" arc
Tongue cylinder	60"
Number of teeth on cutter wheel	48
Chip containment volume	81 cu. Ft.
Cutter wheel diameter with teeth	31"
Cutter wheel thickness	1 1/2"
Jack shaft bearings	2 7/16"
Cutter wheel bearings	2 7/16"
Fuel tank capacity	25 gallons
Hydraulic tank capacity	4 gallons
Tire size	Good Year 235/75-R16
Machine width	80"
Machine height	75"
Machine length	13' 3"
Total weight	4400 lbs.
Paint	Dupont Imron with Epoxy Primer

CARLTON MODEL LINE - UP

Model	Type	Engine	HP	Fuel	Cutting Depth	Cutting Height	Cut Swing	No. Teeth	Wheel Dia.	Wheel Thickness	Tongue Extension	Weight (lbs.)
900H	Walk-Behind	Honda	13	Gas	9"	21"	N/A	12	12.25"	.5"	N/A	220
SP2000	Walk-Behind	Kohler	27	Gas	24"	27"	N/A	16	19"	.5"	N/A	695
SP4012	Self-Propelled	Kohler	27	Gas	13"	34"	40" arc	20	21"	1"	30"	1,550
	Self-Propelled	Briggs-Vanguard	35	Gas	13"	34"	40" arc	20	21"	1"	30"	1,650
	Self-Propelled	Lombardini	28.7	Diesel	13"	34"	40" arc	20	21"	1"	30"	1,650
SP7015	Self-Propelled	Deutz	48	Diesel	15"	43"	70" arc	32	26.5"	1"	N/A	3,500
	Self-Propelled	Deutz Turbo	60	Diesel	15"	43"	70" arc	32	26.5"	1"	N/A	3,500
SP7015TRX	Track-Mounted	Deutz Turbo	60	Diesel	15"	43"	70" arc	32	26.5"	1"	N/A	4,300
SP8018TRX	Track-Mounted	Deutz Turbo	78	Diesel	18"	43"	80" arc	32	26.5"	1"	N/A	5,420
HURRICANE RS	Track-Mounted	John Deere Turbo	140	Diesel	25"	53"	360°	48	31"	1.5"	N/A	8,500
HURRICANE TRX	Track-Mounted	John Deere Turbo	140	Diesel	25"	72"	360°	64	36"	1.5"	N/A	12,000
	Track-Mounted	John Deere Turbo	175	Diesel	25"	72"	360°	64	36"	1.5"	N/A	12,000
	Track-Mounted	John Deere Turbo	250	Diesel	25"	72"	360°	64	36"	1.5"	N/A	12,000
3500D	Tow-Behind	Deutz	48	Diesel	15"	40"	80" arc	32	26.5"	1"	48"	2,900
	Tow-Behind	Deutz Turbo	60	Diesel	15"	40"	80" arc	32	26.5"	1"	48"	2,900
SP7500	Tow-Behind	Deutz Turbo	78	Diesel	24"	46"	92" arc	48	31"	1.5"	60"	4,400

Exceptional Quality & Customer Service

Carlton's commitment to quality can be found in every piece of equipment they manufacture. Each Carlton stump cutter is a result of superior design and the highest quality construction. Plus, Carlton's staff of highly trained and experienced professionals stands behind each stump cutter and is ready with answers to your questions. From parts and service to technical support, Carlton is dedicated to providing the best customer service in the industry. Carlton—Quality products and exceptional service.

Carlton X PROFESSIONAL TREE EQUIPMENT

J.P. Carlton Company • 121 John Dodd Road
Spartanburg, SC 29303
864-578-9335 Fax 864-578-0210

CALL TOLL FREE **800-243-9335** VISIT US ON THE WEB AT **www.stumpcutters.com**